



| | C&I MACH 10® | HP Turbine | TRU/FLO® | HP PROTECTUS® III | HP FST |
|------------------------------------|-------------------------|-------------------|-----------------|--------------------------|---------------|
| Field-replaceable UME | ✓ | ✓ | ✓ | ✓ | ✓ |
| IOM Compatible | ✓ | ✓ | ✓ | ✓ | ✓ |
| Bronze Only Body | ✓ | ✓ | ✓ | ✗ | ✗ |
| Zero Crossover | ✓ | ✓ | ✗ | ✗ | ✓ |
| UL Listed | ✓ | ✗ | ✗ | ✓ | ✓ |
| FM Approved | ✓ | ✗ | ✗ | ✓ | ✓ |
| Ultrasonic Static Technology | ✓ | ✗ | ✗ | ✗ | ✗ |
| No Moving Parts | ✓ | ✗ | ✗ | ✗ | ✗ |
| No Maintenance | ✓ | ✗ | ✗ | ✗ | ✗ |
| Widest Flow Range | ✓ | ✗ | ✗ | ✗ | ✗ |
| Lowest Pressure Loss | ✓ | ✗ | ✗ | ✗ | ✗ |
| Lightest Meter in Class | ✓ | ✗ | ✗ | ✗ | ✗ |
| Horizontal or Vertical Orientation | ✓ | ✗ | ✗ | ✗ | ✗ |
| Excessive Forward Flow Detection | ✓ | ✗ | ✗ | ✗ | ✗ |
| Empty Pipe Detection | ✓ | ✗ | ✗ | ✗ | ✗ |
| Up to 122° F Water Temps | ✓ | ✗ | ✗ | ✗ | ✗ |
| 10 Year Warranty | ✓ | ✗ | ✗ | ✗ | ✗ |